



LOW-PROFILE FAUCET

SKU:532

The low-profile Collins 532 premium faucet is standard equipment on Collins CB19, CB20, and CB23 ABS plastic bowls.

TECHNICAL INFORMATION

- Single handle low profile faucet
- Premium cartridge
- Braided stainless steel supply lines
- Fits most bowl

SHIPPING INFORMATION

Item generally ships via Parcel (Fedex/UPS) service

- Weight: 5 lbs
- Dimensions: 8"L x 6"W x 3"H

WARRANTY

5 YEARS:

- Collins ABS Shampoo Bowls

2 YEARS:



- Collins-Jeffco faucets and Porcelain Shampoo Bowls

1 YEAR:

- All remaining components, unless noted otherwise, are guaranteed for a period of one year from the date of purchase.



532 INSTALLATION



NOTE: Please read these instructions through before starting to familiarize yourself with the components. Any conformance with **LOCAL CODES** or **INSPECTIONS** is the **RESPONSIBILITY OF THE PURCHASER**.

1. We recommend that you install fixtures in the bowl before installing the bowl.
2. Apply a bead of plumbers putty around the fixture hole in the bowl.
3. Place the fixture body on the underside of the fixture hole.
4. From the top side of the bowl, screw the escutcheon onto the fixture.
5. Remove the blue and red button from the front of the handle.
6. Place the handle onto the fixture. Tighten the set screw located in the hole for the button.
7. Replace the button with the red side to the left, blue side to the right.
8. Connect the flexible hoses to the hot and cold supply shut-off valves.
9. Install the vacuum breaker, if so equipped.
10. Connect the Whiz® Spray to the fixture outlet or vacuum breaker. (See bowl instructions.)